

## CLAIMS

What is claimed is:

- 5    ①. A method for externally identifying a particular caller, said method comprising:

receiving a voice utterance for a caller at a server external to a trusted telephone network; and

identifying a caller identity associated with said voice utterance at said server, such that said caller identity is transmittable within said trusted telephone network as an authenticated identity of said caller for a call.

2. The method for externally identifying a particular caller according to claim 1, wherein receiving a voice utterance further comprises:

receiving said voice utterance through a secure channel between said server and said trusted telephone network.

3. The method for externally identifying a particular caller according to claim 1, further comprising:

receiving, at said server, a request for a caller identity authentication service from said trusted telephone network; and

prompting said caller to provide said voice utterance.

4. The method for externally identifying a particular caller according to claim 1, wherein identifying a caller identity further comprises:

5 extracting speech characteristics from said voice utterance;  
and

comparing said speech characteristics with a plurality of voice samples stored for identifying a plurality of callers.

10 5. The method for externally identifying a particular caller according to claim 1, wherein said trusted telephone network comprises at least one public switching telephone network.

15 6. The method for externally identifying a particular caller according to claim 1, wherein said trusted telephone network comprises a private switching system.

20 7. The method for externally identifying a particular caller according to claim 1, further comprising:

accessing said server from said trusted telephone network through an Internet connection.

25 8. The method for externally identifying a particular caller according to claim 1, further comprising:

accessing said server from said trusted telephone network through a private network connection.

9. The method for externally identifying a particular caller according to claim 1, further comprising:

transferring said caller identity to said trusted telephone network through a secure channel.

5

10. A system for externally identifying a particular caller, said system comprising:

a server system communicatively connected to a trusted telephone network by an external network;

means for receiving a voice utterance for a caller at said server system;

means for identifying a caller identity associated with said voice utterance;

means for transmitting said caller identity to said trusted telephone network as an authenticated identity of said caller for a call.

11. The system for externally identifying a particular caller according to claim 10, wherein said means for receiving a voice utterance further comprises:

means for receiving said voice utterance through a secure channel between said server system and said trusted telephone network.

12. The system for externally identifying a particular caller according to claim 10, further comprising:

means for receiving, at said server system, a request for a  
5 caller identity authentication service from said trusted  
telephone network; and

means for prompting said caller to provide said voice  
utterance.

13. The system for externally identifying a particular caller according to claim 10, wherein said means for identifying a caller identity further comprises:

15 means for extracting speech characteristics from said voice  
utterance; and

means for comparing said speech characteristics with a  
plurality of voice samples stored for identifying a plurality of  
20 callers.

14. The system for externally identifying a particular caller according to claim 10, wherein said trusted telephone network comprises at least one public switching telephone network.

15. The system for externally identifying a particular caller according to claim 10, wherein said trusted telephone network comprises a private switching system.

16. The system for externally identifying a particular caller according to claim 10, wherein said external network is the Internet.

5 17. The system for externally identifying a particular caller according to claim 10, wherein said external network is a private network.

10 18. A computer program product for externally identifying a particular caller, said computer program product comprising:  
a recording medium;

15 means, recorded on said recording medium, for enabling receipt of a voice utterance for a caller at a server system communicatively connected to a trusted telephone network via an external network;

means, recorded on said recording medium, for identifying a caller identity associated with said voice utterance;

20 means, recorded on said recording medium, for controlling transmission of said caller identity to said trusted telephone network as an authenticated identity of said caller for a call.

25 19. The computer program product for externally identifying a particular caller according to claim 18, further comprising:

means, recorded on said recording medium, said voice utterance through a secure channel between said server system and

said trusted telephone network.

20. The computer program product for externally identifying a particular caller according to claim 18, further comprising:

5 means, recorded on said recording medium, for enabling receipt at said server system of a request for a caller identity authentication service from said trusted telephone network; and

10 means, recorded on said recording medium, for prompting said caller to provide said voice utterance.

21. The computer program product for externally identifying a particular caller according to claim 18, further comprising:

15 means, recorded on said recording medium, for extracting speech characteristics from said voice utterance; and

20 means, recorded on said recording medium, for comparing said speech characteristics with a plurality of voice samples stored for identifying a plurality of callers.

22. A method for specifying telephone services for a particular caller, comprising:

5 detecting a call initiation condition from an origin device at a trusted telephone network;

brokering a connection between said origin device and an external server enabled to perform a caller identity authentication service; and

10 responsive to receiving, from said external server, an authenticated caller identity of a caller utilizing said origin device, specifying services available to said caller according to said authenticated caller identity.

15 23. The method for specifying telephone services according to claim 22, wherein said server is accessible via a network outside said trusted telephone network.

20 24. The method for specifying telephone services according to claim 22, further comprising:

retrieving a caller profile for said authenticated caller identity; and

25 specifying a selection of services from among a plurality of services that are offered for said call according to said caller profile.

25. The method for specifying telephone services according to claim 22, wherein said authenticated caller identity is authenticated by a voice utterance of said caller.

5 26. The method for specifying telephone services according to claim 22, wherein brokering a connection further comprises:

transmitting a request for said caller identity authentication service via a signal gateway to a network for accessing said external server;

transferring a prompt for a voice utterance, received from said external server via a media gateway, to said origin device;

15 transferring a voice utterance by said caller through said media gateway to said network for accessing said external server; and

20 receiving said authenticated caller identity via said signal gateway at said trusted telephone network.

27. The method for specifying telephone services according to claim 22, wherein brokering a connection further comprises:

25 brokering a secure connection between said trusted telephone network and said external server.



28. A system for specifying telephone services for a particular caller, comprising:

5 a trusted telephone network for providing service to an origin telephony device;

means for detecting a call initiation condition from said origin telephony device at said trusted telephone network;

10 means for brokering a connection between said origin device and a server external to said trusted telephone network to perform a caller identity authentication service; and

15 means responsive to receiving an authenticated caller identity of a caller utilizing said origin telephony device from said server, for specifying services available to said caller according to said authenticated caller identity.

20 29. The system for specifying telephone services according to claim 28, wherein said server is accessible via a network external to trusted telephone network.

30. The system for specifying telephone services according to claim 28, further comprising:

means for retrieving a caller profile for said authenticated  
5 caller identity; and

means for specifying a selection of services from among a plurality of services that are offered for said call according to said caller profile.

31. The system for specifying telephone services according to claim 28, wherein said authenticated caller identity is authenticated by a voice utterance of said caller.

32. The system for specifying telephone services according to claim 28, wherein said means for brokering a connection further comprises:

5 means for transmitting a request for said caller identity authentication service via a signal gateway to a network for accessing said server;

10 means for transferring a prompt for a voice utterance, received from said server via a media gateway, to said origin device;

15 means for transferring a voice utterance by said caller through said media gateway to said network for accessing said server; and

means for receiving said authenticated caller identity via said signal gateway at said trusted telephone network.

33. A computer program product for specifying telephone services for a particular caller, comprising:

a recording medium;

5 means, recorded on said recording medium, for detecting a call initiation condition from an origin telephony device at a trusted telephone network;

10 means, recorded on said recording medium, for brokering a connection between said origin device and a server external to said trusted telephone network to perform a caller identity authentication service; and

15 means, recorded on said recording medium, for specifying services available to said caller according to an authenticated caller identity received from said server to identify a caller utilizing said origin telephony device.

34. A method for informing a callee of a caller identity, comprising:

5 detecting a call initiation condition from an origin device at a trusted telephone network;

brokering a connection between said origin device and an external server enabled to perform a caller identity authentication service; and

10 responsive to receiving, from said external server, an authenticated caller identity of a caller utilizing said origin device, transferring said authenticated caller identity to a destination device, such that a callee receiving said call at  
15 said destination device is provided with an identity of a party originating said call.

35. The method for informing a callee of a caller identity according to claim 34, further comprising:

20 filtering content of said authenticated caller identity before transfer to said destination device.

36. The method for informing a callee of a caller identity  
25 according to claim 35, further comprising:

filtering content of said authenticated caller identity according to filtering preferences associated with said authenticated caller identity.

37. The method for informing a callee of a caller identity according to claim 35, further comprising:

5        filtering content of said authenticated caller identity according to an identity of said callee.

38. The method for informing a callee of a caller identity according to claim 35, further comprising:

10        filtering said authenticated caller identity to block at least a portion of the content of said authenticated caller identity.

15        39. The method for informing a caller of a callee identity according to claim 34, further comprising:

20        responsive to said authenticated caller identity indicating a lack of identity, automatically initiating recording of said call.

40. A system for informing a callee of a caller identity, comprising:

a trusted telephone network for enabling telephone service;

means for detecting a call initiation condition from an origin device at said trusted telephone network;

means for brokering a connection between said origin device and an external server enabled to perform a caller identity authentication service; and

means responsive to receiving an authenticated caller identity of a caller utilizing said origin device from said external server, for transferring said authenticated caller identity to a destination device to identify said caller to a call.

41. The system for informing a callee of a caller identity according to claim 40, further comprising:

means for filtering content of said authenticated caller identity before transfer to said destination device.

42. The system for informing a callee of a caller identity according to claim 41, further comprising:

means for filtering content of said authenticated caller identity according to filtering preferences associated with said

authenticated caller identity.

43. The system for informing a callee of a caller identity according to claim 41, further comprising:

5

means for filtering content of said authenticated caller identity according to an identity of said callee.

44. The system for informing a callee of a caller identity according to claim 41, further comprising:

10

means for filtering said authenticated caller identity to block at least a portion of the content of said authenticated caller identity.

15

45. The system for informing a caller of a callee identity according to claim 40, further comprising:

20

means responsive to said authenticated caller identity indicating a lack of identity, for automatically initiating recording of said call.



46. A computer program product for informing a callee of a caller identity, comprising:

a recording medium;

5

means, recorded on said recording medium, for detecting a call initiation condition from an origin device at a trusted telephone network;

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

means, recorded on said recording medium, for brokering a connection between said origin device and an external server enabled to perform a caller identity authentication service; and

means, recorded on said recording medium, for transferring an authenticated caller identity received from said external server to a destination device to identify said caller utilizing said origin device.

47. The computer program product for informing a callee of a caller identity according to claim 46, further comprising:

means, recorded on said recording medium, for filtering content of said authenticated caller identity before transfer to said destination device.

25

48. The computer program product for informing a callee of a caller identity according to claim 41, further comprising:

means, recorded on said recording medium, for filtering  
5 content of said authenticated caller identity according to filtering preferences associated with said authenticated caller identity.

49. The computer program product for informing a callee of a caller identity according to claim 41, further comprising:

means, recorded on said recording medium, for filtering  
content of said authenticated caller identity according to an  
identity of said callee.

50. The computer program product for informing a callee of a caller identity according to claim 41, further comprising:

means, recorded on said recording medium, for filtering said  
20 authenticated caller identity to block at least a portion of the content of said authenticated caller identity.

51. The computer program product for informing a caller of a callee identity according to claim 46, further comprising:

means, recorded on said recording medium, for automatically  
initiating recording of said call when said authenticated caller  
identity indicates a lack of identity.

52. A method for controlling caller identification, comprising:

receiving, from a trusted telephone network, an  
authenticated caller identity for a caller at a telephony device,  
5 wherein said caller identity is authenticated at a authentication  
service accessible via a network external to said trusted  
telephone network, wherein said trusted telephone network  
initiates said authentication service; and

10 controlling output of said authenticated caller identity  
from said telephony device, such that an individual with access  
to said telephony device is informed of the identity of said  
caller.

15 53. A method for controlling a call, comprising:

receiving, at a telephony device, a secure communication  
channel via a trusted telephone network to an authentication  
service, wherein said trusted telephone network initiates said  
20 authentication service; and

facilitating, from said telephony device, communications  
between said authentication service and a caller, such that said  
authentication service is enabled to authenticate an identity of  
25 said caller.